



**KNITTING**



The consistent growth of the **Group** has been laying on its well-established philosophy which can be summarized by **4 pillars.**



### **Customer Care**

Understanding customer's needs and problems is the key to develop effective solutions. Any new product is the result of the experience gained while working close to over 2000 customers during last 40 years.



### **Intellectual Property**

All products, since LGL was established, have been designed and developed in our own R&D department which nowadays represents more than 10% of the total work force.



### **Efficiency & low environmental impact**

The commitment to sustainable management of resources embraces any step of the process, from design to production, and it's reflected also in the final product which delivers top performances along with high efficiency.

Since 2011 our products are "Green Certified".



### **Continuous innovation**

The path of innovation and updating of the corporate know-how, passes through technological assets in constant evolution, for the protection of which more than 200 international patents have been filed.



## Who we are

LGL is a family-owned group which has its roots in Bergamo province, within one of the most relevant textile industrial districts. The Group, which can account for over 1 million yarn feeders installed since its foundation, comprises 3 companies.

LGL Electronics, established in 1982, is specialized in the development and manufacturing of electronic yarn feeders for weaving and knitting machines.

Elsy, also established in 1982, develops and produces electronics for the textile industry.

LGL Hangzhou which was established in 2004 to expand brand presence in Far East markets through dedicated production, sales and customer service.



Yarn feeder featuring separate coils, suitable for all types of knitting machines or for textile machines requiring yarn feed-in with constant tension.

**ECOMPACT2**


**ECOPOWER2**



Attivo



Attivo



Coax



Coax

<b>Features</b>	Visible status light	
	Automatic speed adjustment	
	Winding reserve control	
	Empty bobbin "machine stop" function	
	Self calibration	
	Mechanical yarn output detection - machine stop	
	Easy setting of cams (large diameter machines) - YSC function	
<b>Range of yarns</b>	5 to 600 Den	5 to 800 Den
<b>Spool body diameter</b>	52 mm	69 mm
<b>Tension range</b>	0,5 to 25 cN	0,5 to 45 cN
<b>Speed</b>	up to 700 m/min	up to 1000 m/min
<b>Braking systems</b>	Coax, Attivo	Coax, Attivo, Brake
<b>Coil separation</b>	0,9 mm	1 mm
<b>Max. power consumption</b>	30 W	35 W
<b>Power supply</b>	AC, DC	
<b>Communication</b>	RS-485, CAN Bus, Modbus	
<b>Weight</b>	Coax 1,4 Kg	Coax 2,2 Kg
	Attivo 1,5 Kg	Attivo 2,3 Kg
		Brake 2,6 Kg

**Main applications**

Large diameter Circular knitting, Socks, Seamless, Flat knitting

Certified





## COAX

Manual tension adjustment.  
Guarantees quick, easy and repeatable setting.



## ATTIVO & BRAKE

Tension is set through software. Attivo will keep the desired tension constant over the time.

No tension changes due to different bobbins diameters.

No tension changes during transition from full to empty bobbin.

Tension set from 0 TO 50 cN with ATTIVO and up to 200 cN with Brake:.



0 TO 50 Attivo



0 TO 200 Brake

## SPIN2

Yarn feeder featuring separate coils, suitable for all types of knitting machines or for textile machines requiring yarn feed-in with constant tension. Dedicated wheels available depending on yarn properties or application.



For winders



Water-resistant



Slippery yarns



Yarn recovery



For elastic yarns

<b>Features</b>	Visible status light
	Quick reaction to set tension changes
	Quick reaction to machine speed changes without tension peaks on yarn
	Maximum torque available also at low speeds
	Yarn absorption measurement
	Ceramic tension sensor: guarantees accuracy, precision and reactivity
	Automatic speed control up to 1400 m/min
	Yarn absorption speed measurement
Yarn retrieving up to 150 mm	
<b>Range of yarns</b>	Bare & covered elastomeric
<b>Wheel diameter</b>	50 mm
<b>Tension range</b>	0,5 to 100 cN
<b>Coil separation</b>	0 to 2 mm
<b>Power consumption</b>	Avg. 5 to 15 W
<b>Power supply</b>	24VDC ± 10% to 60VDC ± 10%
<b>Communication</b>	RS 485, CAN bus, MOD BUS
<b>Interface</b>	Integrated display & buttons

### Main applications

Socks, seamless, Flat knitting, Winders


Certified



## TWIN

Up to 4 devices can be installed in a single cluster to save space and wiring- yarn recovery.

Dedicate wheel for rigid yarn allows yarn recovery function.



Single

Double

Triple

<b>Features</b>	Quick reaction to set tension changes
	Quick reaction to machine speed changes without tension peaks on yarn
	Maximum torque available also at low speeds
	Yarn consumption measurement
	Ceramic tension sensor: guarantees accuracy, precision and reactivity
	Automatic speed control up to 1400 m/min
	Easy setting of machine cams (large diameter machines) - SYF function
	Yarn retrieving up to 150 mm
<b>Range of yarns</b>	10 to 800 Den and Bare & covered elastomeric
<b>Wheel diameter</b>	43 mm
<b>Tension range</b>	0,5 to 50 cN (100 and 200 cN optional)
<b>Coil separation</b>	Adjustable
<b>Power consumption</b>	Avg. 5 to 15 W
<b>Power supply</b>	24VDC ± 10% to 60VDC ± 10%
<b>Communication</b>	CAN bus
<b>Interface</b>	Requires KYC/Feederlink



Yarn recovery



For elastic yarns

### Main applications

Large Diameter Circular knitting, Warpings

Certified



## REEL

Yarn retrieving device to be installed on Ecopower2 or Ecompact2 feeders keeps yarn tension constant between feeder and machine Retrieve up to 1 m of yarn.



Load cell range	0 to 100 cN
Yarn range	5 to 800 Den
Communication	CAN BUS
Weight	220 g
Dimensions	152 × 65 × 82 mm

**Main applications**  
Flat knitting

## IFS Tension sensor

Yarn tension measurement sensor based on ILC (inductive Load Cell) technology. Its compact dimension allows the installation at any step of yarn process.

Available tension range	50-100-250-500-1000 cN
Supply voltage	12-24 VDC
Output voltage	0-10 VDC
Dimensions	50 × 27,5 × 29 mm



### Key features

- **Low stress on the yarn**  
Internal geometry of the sensor has been designed to minimize the stress delivered to the yarn while passing through with no compromise on the measurement accuracy.
- **Not sensitive to dust**  
ILC technology allows reliable and precise measure regardless of dust accumulation.

**Main applications**  
Winders



## KYC TOUCH



## FEEDER LINK



	On-board machine control simultaneously all feeders installed. It allows the same functions by laptop/tablet (USB) and customer ERP (wifi - ethernet)	On-board machine control one-by-one any feeders installed. It allows simultaneous control of all feeders by laptop/tablet
	Save and upload machine configuration	
	KLS - automatic machine stop upon yarn breakage detection after the feeder	
<b>Features</b>	YCM yarn consumption information	YCM (by laptop/tablet) yarn consumption information
	YCC - automatic machine stop if yarn consumption is out of a pre-set range	
	YSC - Synchronized yarn consumption for selected group of storage feeders	
	SYF - Synchronized yarn consumption for selected group of positive feeders	-
	Remote interactive Technical assistance	-
	Predictive maintenance	-
<b>Main interface</b>	7" touch screen	1" 1/4 LCD
<b>Feeders compatibility</b>	Ecompact2, Ecompact2, Twin, Spin	
<b>Suitable for</b>	Large diameter knitting machines Warping	Flat knitting, large diameter Socks & seamless machines
<b>Available Connections to laptop</b>	USB - ETHERNET - WI-FI	USB

All Feeders	Group All	YCM	YCC
1-10000000 Group 0 Item Inn: 10000.00 Out: 10000.00	1-10000000 Group 01 Item Inn: 10000.00 Out: 10000.00	1-10000000 Group 01 Item Inn: 10000.00 Out: 10000.00	1-10000000 Group 01 Item Inn: 10000.00 Out: 10000.00

All Feeders	Group All	YCM
1-10000000 Group 01 Item Inn: 10000.00 Out: 10000.00	1-10000000 Group 01 Item Inn: 10000.00 Out: 10000.00	1-10000000 Group 01 Item Inn: 10000.00 Out: 10000.00

Suggested applications



	Flat knitting	Sock	Seamless	Large Diameter	Warpers	Winders
Ecopower2 Coax	●	●	●	Electronic jacquard		●
Ecopower2 Attivo		●	●	Electronic jacquard		
Ecopower2 Brake				Electronic jacquard		
Ecopower2 Reel	Recovery up to 70 cm					
Ecompact2 Coax	●	●	●	●		●
Ecompact2 Attivo	●	●	●	●		
Twin				Bare spandex	●	
Twin Recovery wheel	Recovery up to 15 cm	●		Hard yarns on fine gauges, striper		
Spin2		●	●			●
Spin2 Recovery wheel	Recovery up to 15 cm					



[www.lgl.it](http://www.lgl.it)



**LGL Electronics S.p.A.**

Via Ugo Foscolo,156 - 24024 Gandino (BG) - Italy  
T +39 035 733408 F +39 035 733146  
lgl@lgl.it www.lgl.it